

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

IN THE CLAIMS

Please amend claims 1-23 as follows. This listing of claims replaces all prior versions, and listings, of claims in the application:

Claim 1 (currently amended): A dosing device in a dispensing machine which dispensing machine comprises a magnetization unit for generating a changing magnetic field, said dosing device comprising a housing comprising at least one inlet, at least one outlet, a liquid flow path extending from the inlet to the outlet, and a pump included in the liquid flow path, the dosing device being adapted for dispensing in a metered manner a viscous concentrate from a holder in which the concentrate is contained, the concentrate in diluted form giving a product suitable for consumption, the holder comprising a storage space in which the concentrate is contained, and the inlet of the dosing device being adapted to be connected, in use, to the storage space of the holder, ~~characterized in that~~ wherein the dosing device comprises a rotor rotatably ~~mounted~~ connected to the housing for rotation around a rotation axis, for causing the rotor to rotate about the rotation axis ~~by means of a~~ in response to the changing magnetic field of said magnetization unit, the ~~rotor pump~~ being mechanically connected to the ~~pump rotor~~ rotor for driving the pump ~~with the rotating in response to the rotation of the rotor~~ by changing the magnetic field.

Claim 2 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the rotor is included in the liquid flow path.

Claim 3 (currently amended): A dosing device according to claim 2, ~~characterized in that~~ wherein the rotor is included in the liquid flow path upstream of the pump.

Claim 4 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the rotor is provided with a magnetizable material such as soft iron.

Claim 5 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the rotor comprises a permanent magnet for contactlessly driving the rotor by means of at least one magnetic field.

Claim 6 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the rotor comprises a plurality of arms extending in radial direction of the rotation axis.

Claim 7 (currently amended): A dosing device according to claim 5, ~~characterized in that~~ wherein the ends of the arms form poles of the permanent magnet.

Claim 8 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the pump is driven by the rotor by way of a drive shaft of which an axial axis is directed in a direction from the inlet to the outlet.

Claim 9 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the housing of the dosing device is of substantially rotation-symmetrical design, with an axial axis of the housing extending in the direction from the inlet to the outlet.

Claim 10 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the dosing device is provided, downstream of the pump, with a valve included in the liquid flow path, which opens when the liquid pressure upstream of the valve exceeds a predetermined threshold valve.

Claim 11 (currently amended): A dosing device according to claim 1, ~~characterized in that~~ wherein the pump is constructed as a gear pump.

Claim 12 (currently amended): A holder ~~filed for filling~~ with concentrate, which in diluted form, is suitable for consumption, the holder ~~comprises~~ comprising a dosing device according to claim 1.

Claim 13 (currently amended): A holder according to claim 12, ~~characterized in that~~ wherein the holder comprises a bag formed from a flexible sheetlike material in which the concentrate is contained, and a housing in which the bag is received.

Claim 14 (currently amended): A holder according to claim 13, ~~characterized in that~~ wherein the inlet of the dosing device is connected to the bag.

Claim 15 (currently amended): A holder according to claim 12, ~~characterized in that~~ wherein the housing is of more rigid design than the bag.

Claim 16 (currently amended): An apparatus for preparing a beverage suitable for consumption, the apparatus being adapted to be loaded with a holder for filling with concentrate, which in diluted form, is suitable for consumption, the holder comprising a dosing device for placement in a dispensing machine, the dosing device comprising a magnetization unit for generating a changing magnetic field comprising a housing comprising at least one inlet, at least one outlet, a liquid flow path extending from the inlet to the outlet, and a pump included in the liquid flow path, the dosing device being adapted for dispensing in a metered manner a viscous concentrate from a holder in which the concentrate is contained, the concentrate [is] in diluted form giving a product suitable for consumption, the holder comprising a storage space in which the concentrate is contained, and the inlet of the dosing device being adapted to be connected, in use, to the storage space of the holder, ~~characterized in that~~ wherein the dosing device comprises a rotor rotatably connected to the housing for rotation around a rotation axis, for causing the rotor to rotate about the rotation axis by means of the changing magnetic field, the rotor being mechanically connected to the pump for driving the pump with the rotating rotor, the apparatus comprising a magnetization unit for generating at least one magnetic field changing such that the rotor is contactlessly driven by the magnetization unit for the dosing device to dispense concentrate from the holder in a metered manner, and ~~means for diluting a diluter for~~ the dispensed concentrate with water for obtaining the beverage suitable for consumption.

Claim 17 (currently amended): An apparatus according to claim 16, ~~characterized in that~~ wherein the magnetization unit comprises a magnet and ~~driving means~~ a driver for rotating the magnet for generating the changing magnetic field.

Claim 18 (currently amended): An apparatus according to claim 16, ~~characterized in that~~ wherein the magnetization unit comprises a plurality of coils.

Claim 19 (currently amended): An assembly comprising an apparatus for preparing a beverage suitable for consumption and a holder according to claim 12, the apparatus being loaded with the holder, and the apparatus comprising ~~driving means~~ a driver for driving the dosing device for the dosing device to dispense concentrate from the holder in a metered manner, and ~~means for diluting~~ a diluter for the dispensed concentrate ~~with water~~ for obtaining the beverage suitable for consumption.

Claim 20 (currently amended): An assembly according to claim 19, ~~characterized in that~~ wherein the holder is detachably connected to the apparatus.

Claim 21 (currently amended): An assembly ~~according to claim 19 comprising an apparatus for preparing a beverage suitable for consumption and a holder for filling with concentrate, which in diluted form, is suitable for consumption,~~ wherein the holder comprises a dosing device for placement in a dispensing machine which comprises a magnetization unit for generating a changing magnetic field, the dosing device comprising a housing comprising at least one inlet, at least one outlet, a liquid flow path extending from the inlet to the outlet, and a pump included in the liquid flow path, the dosing device being adapted for dispensing in a metered manner a viscous concentrate from [a] the holder in which the concentrate is contained, the concentrate is diluted form giving a product suitable for consumption, the holder further comprising a storage space in which the concentrate is contained, and the inlet of the dosing device being adapted to be connected, in use, to the storage space of the holder, ~~characterized in that~~ wherein the dosing device comprises a rotor rotatably connected to the housing for

rotation around a rotation axis, for causing the rotor to rotate about the rotation axis by means of the changing magnetic field, the rotor being mechanically connected to the pump for driving the pump with the rotating rotor, characterized in that the apparatus further comprises a magnetization unit for generating at least one magnetic field changing such that the rotor is driven for causing the dosing device to dispense concentrate from the holder, the apparatus being loaded with the holder, and the apparatus further comprising a driver for driving the dosing device for the dosing device to dispense concentrate from the holder in a metered manner, and a diluter for the dispensed concentrate with water for obtaining the beverage suitable for consumption.

Claim 22 (currently amended): An assembly according to claim 21, characterized ~~in that~~ wherein the magnetization unit comprises a magnet and ~~driving means~~ a driver for rotating the magnet for generating the changing magnetic field.

Claim 23 (currently amended): An assembly according to claim 21, characterized ~~in that~~ wherein the magnetization unit comprises a plurality of coils.